

GPS/GLONASS Personal Tracker

MT90



Specifications

Item	Specifications
Dimension	77 mm x 47 mm x 20 mm
Weight	70g
Charging voltage	Micro USB charging port, DC 4.2 V~5.5 V/400 mA
Standby battery	1100 mAh/3.7 V rechargeable and replaceable lithium-ion battery (Nokia BL-5C compatible)
Power consumption	60 mA standby current and 5 mA deep sleep
Operating temperature	-20°C to 55°C
Humidity	5%~95%
Working hour	160 hours in power-saving mode and 14 hours in normal mode
LED indicator	2 indicators showing power, GSM, and GPS status
Button/Switch	5 buttons/switches
Microphone/Loudspeaker	Internal microphone and loudspeaker
Memory	8 MB byte (130,000 GPS Logs, 8,000 GPRS caches, and 256 SMS caches)
Sensor	3D acceleration sensor
GSM frequency band	GSM 850/900/1800/1900 MHz
Positioning accuracy	10m



Personal tracking



Vehicle tracking



Asset tracking



Fleet management

Specifications

Item	Specifications
Dimension	77 mm x 47 mm x 20 mm
Weight	70g
Charging voltage	Micro USB charging port, DC 4.2 V–5.5 V/400 mA
Standby battery	1100 mAh/3.7 V rechargeable and replaceable lithium-ion battery (Nokia BL-5C compatible)
Power consumption	60 mA standby current and 5 mA deep sleep
Operating temperature	-20°C to 55°C
Humidity	5%–95%
Working hour	160 hours in power-saving mode and 14 hours in normal mode
LED indicator	2 indicators showing power, GSM, and GPS status
Button/Switch	5 buttons/switches
Microphone/Loudspeaker	Internal microphone and loudspeaker
Memory	8 MB byte (130,000 GPS Logs, 8,000 GPRS caches, and 256 SMS caches)
Sensor	3D acceleration sensor
GSM frequency band	GSM 850/900/1800/1900 MHz
Positioning accuracy	10m